


3M™ Round Conductor Flat Cable

.025" 30 AWG Solid, Halogen-Free Insulation

2049 Series



- Advantages of this halogen free insulation are low smoke (BSS 7238) and low toxicity of combustion gases (NES 713) reducing risk to firefighters and low corrosivity of combustion gases (pH≈6.0) reducing damage to nearby equipment.
- 30 AWG solid conductors on .025 inch pitch permits higher signal density and mass-termination.
- Please contact your 3M sales representative for variations not described in this specification.
- See Regulatory Information Appendix (RIA) for chemical compliance information (RIA E1 & C1 apply)

Date Modified: May 5, 2009

TS-0886-D
Sheet 1 of 2

Physical

Insulation:

Material: Halogen-Free Polyolefin (PO) Appendix C1 & E1 apply.

Color: Off-White

Marking:

Standard: None

Conductors: 30 AWG [Ø 0.025"] Tinned Solid Copper

Electrical

Voltage Rating: USA: 30V

EU: <50V

Insulation Resistance: (Primary Cable) $> 1 \times 10^{10} \Omega/10 \text{ ft. [3 m]}$

Characteristic Impedance: Unbalanced
83 Ω

Balanced
137 Ω

Capacitance: 19.0 pF/ft [62.3 pF/m]

11.1 pF/ft [36.4 pF/m]

Inductance: 0.13 $\mu\text{H}/\text{ft}$ [0.43 $\mu\text{H}/\text{m}$]

0.21 $\mu\text{H}/\text{ft}$ [0.66 $\mu\text{H}/\text{m}$]

Propagation Delay: 1.58 ns/ft [5.18 ns/m]

1.52 ns/ft [4.99 ns/m]

Velocity of Propagation: 64%

67%

Note: Unbalanced is measured between ground-signal-ground conductors.

Environmental

Temperature Rating: -20°C to +105°C

Flammability Rating: USA: UL: Horizontal

UL File No.: E42769, Style No: 20930


3M™ Round Conductor Flat Cable

.025" 30 AWG Solid, Halogen-Free Insulation

2049 Series



Number of Conductors	3M Part Number	Dimension A	Dimension B
20	2049/20	0.500 ± .006 [12.70]	0.475 ± .004 [12.07]
26	2049/26	0.650 ± .006 [16.51]	0.625 ± .004 [15.88]
34	2049/34	0.850 ± .009 [21.59]	0.825 ± .006 [20.96]
36	2049/36	0.900 ± .009 [22.86]	0.875 ± .006 [22.23]
40	2049/40	1.000 ± .009 [25.40]	0.975 ± .006 [24.77]
50	2049/50	1.250 ± .009 [31.75]	1.225 ± .006 [31.12]
60	2049/60	1.500 ± .012 [38.10]	1.475 ± .009 [37.47]
68	2049/68	1.700 ± .012 [43.18]	1.675 ± .009 [42.55]
80	2049/80	2.000 ± .015 [50.80]	1.975 ± .011 [50.17]
100	2049/100	2.500 ± .015 [63.50]	2.475 ± .012 [62.87]



Note:

- Blue marking on one edge of cable designates wire #1.

Inch
[mm]

Tolerance Unless Noted			
	.0	.00	.000
Inch	±.1	±.01	±.005

[] Dimensions for Reference Only

Ordering Information

2049/XX XX

Number of Conductors
(See Table)

Blank = Standard
SF = Splice Free

Note:

- Available in standard lengths of 30 m and 100 m per roll, please specify when ordering.

TS-0886-D
Sheet 2 of 2

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**



3M Electronics Solutions Division

6801 River Place Blvd.
Austin, TX 78726-9000
U.S.A.
1-800-225-5373
www.3Mconnector.com

Please recycle. Printed in USA.
© 3M 2010. All rights reserved.
RIA-2217B-E

3M is a trademark of 3M Company.