

PRODUCT NUMBER

20020620-MXXXXXXLF

20020620-□ □ □ □ A 0 □ L F

PITCH
M: 7.62 mm

POLES

02: 2 POLES
03: 3 POLES
04: 4 POLES

16: 16 POLES

LF : DENOTED RoHS COMPATIBLE

1 : STANDARD PRODUCT
W/ BOX PACKING

HOUSING CODE

CODE	COLOR	AVAILABILITY
1	GREEN(RAL 6018/T)	STANDARD
2	BLACK	ON REQUEST ONLY
3	GREY(RAL 7004/P)	ON REQUEST ONLY
4	BLUE(RAL 5015/A)	ON REQUEST ONLY

PROPERTY TABLE

FCI SERIES NAME	07-762
PITCH (mm)	7.62
VOLTAGE RATING (VAC)	300
CURRENT RATING (A)	32
WITHSTANDING VOLTAGE (kV)	1.6
OPERATING TEMP. (°C)	-40~+115
SOLDERING TEMP. (°C)	250±10 (5 sec.)
POLES AVAILABLE	02~16
SAFETY CERTIFICATE	

NOTES:

MATERIALS

1-1 HOUSING: THERMALPLASTIC RESIN, UL 94V-0 RATED.

1-2 TERMINAL: COPPER ALLOY, TIN PLATED.

2. PRODUCTION SPECIFICATION REFER TO FCI GS-12-625.

3. BOXED PACKAGING.

DETAILED PRODUCT PACKING SPECIFICATION REFER TO FCI GS-14-1394.


4. FCI, SAFETY CERTIFICATE LOGO AND SERIES NAME TO BE SHOWN ON PRODUCT SURFACE.

5. THE PRODUCTS WHERE THE PART NUMBER END IN "LF" MEET THE EUROPEAN UNION DIRECTIVE AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.

6. RECOMENDED SOLDERING PROCESS BY WAVE SOLDER.



mat'l. code				surface ASME Y14.5 ✓	tolerance ASME Y14.5	projection 	product family TERMINAL BLOCK
ltr	ecn no	dr	date	tolerances unless otherwise specified			title
A	0609-0203	BF	062509	angles	X.±0.5[.020]	MM [INCH]	TERMINAL BLOCK
B	T09-1148	BF	111709	to file	X.X±0.3[.012]		PLUGGABLE SOCKET, STRAIGHT
C	T10-0042	WL	030310	X*±1*	X.XX±0.1[.004]	scale	dwg no
D	T10-0159	WL	100410	dr	BEER FU	062509	sheet 1 of 2 size
E	T10-0187	WL	121410	enr	BEER FU	062509	20020620
F	T-004746	WL	072211	chr	GARY HSIEH	062509	A4
G	T-005754	WL	090611	appd	JOSEPH HSIA	062509	type
sheet	revision	G	G				CUSTOMER Drawing
index	sheet	1	2				

PRODUCT NUMBER	SERIES NAME	PITCH
20020620-MXXXXXXLF	07-762	7.62 mm




N = Number of poles
 Dim L = $N \times 7.62$ [.300]
 Dim B = $(N-1) \times 7.62$ [.300]

Poles	Tol.	Dim L	Dim B
2-5p		± 0.20 [.008]	
6-10p		± 0.25 [.010]	
11-13p		± 0.35 [.014]	
14-16p		± 0.40 [.016]	



SECTION P-P



P.C.B LAYOUT

mat'l. code				surface ASME Y14.5 ✓	tolerance ASME Y14.5	projection MM INCH	product family TERMINAL BLOCK
ltr	ecn	no	dr	date	tolerances unless otherwise specified		title
G					angles	X. ±0.5 [.020] X.X ±0.3 [.012] X.XX ±0.1 [.004]	TERMINAL BLOCK PLUGABLE, SOCKET, POWER, VERTICAL
					dr	BEER FU 062509	dwg no
					enr	BEER FU 062509	sheet 2 of 2
					chr	GARY HSIEH 062509	size
					appd	JOSEPH HSIA 062509	A4
sheet index	revision	sheet					type
							CUSTOMER Drawing