


## data sheet

<b>system:</b>	Lithium-Ion-Battery	
<b>nominal voltage:</b>	3.7V	
<b>end charge voltage:</b>	4.2V	
<b>max. charge current:</b>	750mA	
<b>charge conditions</b>		
standard charge:	325mA	for 3.5h min.
fast charge:	650mA	for 2.5h min.
charging method:	CC-CV (constant current and constant voltage)	
<b>capacity</b>	after standard charge	
nominal:	750mAh	at 0.2C discharge to 2.75V
minimal:	750mAh	at 0.2C discharge
	675mAh	at 1C discharge
<b>energy:</b>	2.8Wh	
<b>max. continuous discharge current:</b>	750mA	
internally safety system:	protection circuit board (pcb) with protection against overcharge, deep discharge and overload	
<b>life time expectancy:</b>	> 300 cycles	
<b>ambient temperature range</b>		
charge:	0...45°C	
discharge:	-20...60°C	
long term storage:	-20...35°C (less than 1 year)	
<b>QCT3:</b>	620/590	
<b>weight:</b>	approx. 20g	
<b>dimensions:</b>	L1: 41.7 ± 0.3mm L2: 34.7 ± 0.3mm L3: 7.2 ± 0.2mm	



	Specifications for model/type:	A – Can NB-6L
	Ansmann drawing number / part number:	5044453
	supplier no.:	701556
	author / date:	TG / 23.10.2013