


LF1206C202R-10

**UNCONTROLLED
DOCUMENT**

PHYSICAL DIMENSIONS:

A	3.20 [.126]	+0.20 [.008]
B	1.60 [.063]	+0.20 [.008]
C	1.10 [.043]	+0.20 [.008]
D	0.51 [.020]	+0.25 [.010]





ELECTRICAL CHARACTERISTICS:


Z @ 30MHz (Ω)	DCR (Ω)	Rated Current
Nominal	2000	
Minimum	1500	
Maximum	2500	0.50
		300 mA

NOTES: UNLESS OTHERWISE SPECIFIED

1. TAPED AND REELED per CURRENT EIA SPECIFICATIONS 7" REELS, 3000 PCS/REEL, EMBOSSED PLASTIC TAPE.
2. TERMINATION FINISH IS 100% TIN.
3. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.




LAND PATTERNS FOR REFLOW SOLDERING



(For wave soldering, add 0.762 [.030] to this dimension)

RECOMMENDED SOLDERING CONDITIONS



DIMENSIONS ARE IN mm [INCHES]				This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.			
				Laird TECHNOLOGIES			
PROJECT/PART NUMBER:				REV	PART TYPE:	DRAWN BY:	
LF1206C202R-10				B	CO-FIRE	JRK	
B	UPDATE COMPANY LOGO	07/08/08	JRK	DATE:	09/13/06	SCALE:	NTS
A	ORIGINAL DRAFT	09/13/06	JRK	CAD #		TOOL #	
REV	DESCRIPTION	DATE	INT	LF1206C202R-10-B			