

MATERIALS AND FINISHES

BODY BRASS
PLATED GOLD

CENTER CONTACT BRASS
PLATED GOLD

INSULATOR TEFLON

MMCX PLUG
INTERFACE

0.13±0.13
.005±.005

15.32
.603 REF

2.67
.105 HEX

RG178 CABLE

12.68
.499 REF

3.89
.153 REF

5.23
.206 REF

0.40
.016 REF

CONTACT

7.01
.276 REF

3.15
.124 REF

CRIMP TUBE

9.17

.361

4.67

.184

1.19

.047

RG-178

RECOMMENDED CABLE STRIP

CECC 22 340

INTERFACE

PS-89675-1920

ELECTRO/MECH. PERFORM.

SPECIFICATION

DESCRIPTION

ADDED 73415-0973
PER PDR13111484

EC NO: URF2014-0356
2013/12/10
DRWN:LIN

CHKD:
APPR:MHUANG

2013/12/18
DESCRIPTION

B3

QUALITY
SYMBOLS

0

0

GENERAL TOLERANCES
(UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± .---	± .---
3 PLACES	± .---	± .---
2 PLACES	± .---	± .---
1 PLACE	± .---	± .---

ANGULAR ± 2 °

DRAFT WHERE APPLICABLE
MUST REMAIN
WITHIN DIMENSIONS

DIMENSION STYLE
MM/IN

DRAWN BY	DATE
TEF	1999/02/15
CHECKED BY	DATE
JOHNSON	2004/06/04
APPROVED BY	DATE
MISEN	2004/06/04

SEE TABLE

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX
INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

SCALE

DESIGN UNITS
METRIC

THIRD ANGLE
PROJECTION

MMCX PLUG, STRAIGHT
50 OHMS, FOR RG178 CABLE
MMCX-PC

MOLEX INCORPORATED

DOCUMENT NO.

SD-73415-097

SHEET NO.
1 OF 1