



TECHNICAL DATASHEET

Cyanolit® 241

Cyanolit® 241 is a low viscosity, fast curing adhesive with excellent wettability .

Cyanolit® with it's universal adhesive features bonds plastics metal rubber and low density syntactic foam, either similar or dissimilar materials, together.

Cyanolit® 241 is also available in a small dosing dispenser bottle.

Technical Data

Color	transparent
Resin	Ethyl-2-Cyanacrylat
Gap Width max	0,15 mm

UNCURED PROPERTIES

Viscosity (Brookfield LVT/25°C) [mPa*s]	40
Flash point [°C]	> 83

Tensile Strength/SETTING TIME

PVC hart	8	seconds	5,2 °	MPa
ABS	12	seconds	5,4 °	MPa
PA 6.6	22	seconds	4,2	MPa

°material breakage

CURED PROPERTIES

Temperature Resistance	-80 to 80 °C
------------------------	--------------

Our data sheets have been compiled to the best of our knowledge. The information included in our data sheets is exclusive information for the tended user and describes characteristics, with no declaration of commitment. We recommend trials in order to confirm that our products satisfy the particular application requirements. For an additional technical consultation, please contact our RD department. In general, for guarantee claims, please refer to our standard terms and conditions.

Adhesives
and more...