

REV. Status

REVISION -
07/30/86 MS


REVISION A
REVISED AND
REDRAWN ON
CAD/CAM
03/27/92 TS

REVISION B
NEW FORMAT.
TEMECULA
WAS CARSON
REVISED DIM
19.05±0.5
(0.75±0.02)
-WAS-
6.35±0.5
(0.25±0.02)
05/13/98 TS

LOW PROFILE TELECOMMUNICATION COUPLING TRANSFORMER

A. Electrical Specifications (@ 25°C)

1. Pri Source Impedance; 600 Ω Shielded
2. Sec Load Impedance; 600 Ω
3. Sec DC Current; 120mA MAX (5-8)
4. Operating Level; -45dBm to +7dBm
5. Insertion Loss;
1.3dB TYP 1.5dB MAX @ 1KHz, 0dBm, DC120mA
6. Frequency Response; (relative to 1KHz)
±0.5dB @ 300Hz to 3.5KHz, 0dBm, DC120mA
7. Return Loss;
18dB TYP @ 1KHz, 0dBm, DC120mA
8. Longitudinal Balance; 60dB MIN @ 200Hz to 4KHz
9. Total Harmonic Distortion; 0.1% MAX @ 300Hz, 0dBm, DC120mA
10. DC Resistance;
(1-4) = 57.5Ω ±15%
(5-8) = 99.0Ω ±15%
11. Turns Ratio;
(1-4) : (5-8) = 1 : 1.10
12. Dielectric Strength;
2200VDC 1 minute @ Pri to Sec, Pri to Shield, Sec to Shield




MODEL NUMBER

TTC-160


Date code and country of origin

B. Marking; TTC-160, TAMURA, date code and country of origin

C. Schematic Diagram



D. Mechanical Specifications



PREPARED BY:

D. Rund

ENGINEER:

T. Shiozawa

QUALITY CONTROL:

D. Kelley

APPROVED:

D. Kelley

DRAWING CONTROL NO.
P-A1-10183
ACAD\TTC\A1101831.DWG

REV

B

MODEL DESCRIPTION
TELECOMMUNICATION COUPLING
TRANSFORMER

TAMURA CORPORATION OF AMERICA

43352 BUSINESS PARK DRIVE, TEMECULA, CA. 92590-6624
(909) 699-1270 FAX 9096769482

MODEL SPECIFICATION

TTC-160

DIM: mm(In) SCL: 1/1 SH: 1 OF 1

PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING.