

LOC	DIST	REVISIONS					
A1	-	P	LYR	DESCRIPTION	DATE	DWN	APVD
				SEE SHEET 1 OF 2			
TFD							

21	6	38.5	30	45	42.5	38.5	36.5	B (GROOVES) Nuten A-C A (GROOVES B-C) (Nuten B_C)		5-966140-6 A 	4-966140-6 A 	18.3g	4	7	TAB (43.4mm)	CuSn0.15/0.20	SEL. SILVER PLATED			
									3	7	TAB (34.4mm)		CuSn0.15/0.20	SEL. SILVER PLATED						
									2	7	TAB (25.4mm)		CuSn0.15/0.20	SEL. SILVER PLATED						
									5	1	21 POS. HOUSING		PA66-GF13	NATURAL/natur						
18	5	33.5	25	40	37.5	33.5	31.5			6-966140-6 C 	3-966140-6 C 	18.3g	4	7	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED			
									3	7	TAB (34.4mm)		CuSn4	SEL. SILVER PLATED						
									2	7	TAB (25.4mm)		CuSn4	SEL. SILVER PLATED						
									1	1	21 POS. HOUSING		PA66-GF13	BLACK/schwarz						
15	4	28.5	20	35	32.5	28.5	26.5			6-966140-1 C 	3-966140-1 C 	16.0g	4	6	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED			
									3	6	TAB (34.4mm)		CuSn4	SEL. SILVER PLATED						
									2	6	TAB (25.4mm)		CuSn4	SEL. SILVER PLATED						
									1	1	18 POS. HOUSING		PA66-GF13	BLACK/schwarz						
12	3	23.5	15	30	27.5	23.5	21.5		6-966140-2 C 	3-966140-2 C 	13.6g	4	5	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED				
								3	5	TAB (34.4mm)		CuSn4	SEL. SILVER PLATED							
								2	5	TAB (25.4mm)		CuSn4	SEL. SILVER PLATED							
								1	1	15 POS. HOUSING		PA66-GF13	BLACK/schwarz							
9	2	18.5	10	25	22.5	18.5	16.5		6-966140-3 C 	3-966140-3 C 	11.2g	4	4	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED				
								3	4	TAB (34.4mm)		CuSn4	SEL. SILVER PLATED							
								2	4	TAB (25.4mm)		CuSn4	SEL. SILVER PLATED							
								5	1	12 POS. HOUSING		PA66-GF13	NATURAL/natur							
6	1	13.5	5	20	17.5	13.5	11.5		6-966140-4 C 	3-966140-4 C 	8.9g	4	3	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED				
								3	3	TAB (34.4mm)		CuSn4	SEL. SILVER PLATED							
								2	3	TAB (25.4mm)		CuSn4	SEL. SILVER PLATED							
								1	1	9 POS. HOUSING		PA66-GF13	BLACK/schwarz							
POSITIONS Polzahl	n	a±0.2	b	c	d _{-0.2}	e _{-0.25}	f	CODING Kodierung		6-966140-5 C 	3-966140-5 C 	6.6g	4	2	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED			
													3	2	TAB (34.4mm)	CuSn4	SEL. SILVER PLATED			
													2	2	TAB (25.4mm)	CuSn4	SEL. SILVER PLATED			
													1	1	6 POS. HOUSING	PA66-GF13	BLACK/schwarz			
															POS.		QTY Stueck	DESCRIPTION Benennung Einzelteil	MATERIAL Werkstoff	SURFACE/Oberflaeche
																				COLOUR/ Farbe

21	6	38.5	30	45	42.5	38.5	36.5	B (GROOVES) Nuten A-C A (GROOVES B-C) (Nuten B-C)		8-966140-6 A		1-966140-6 A		18.3g	4	7	TAB (43.4mm)	CuSn4	TINNED/verzinkt	
										9-966140-6 F		966140-6 F			3	7	TAB (34.4mm)	CuSn4	TINNED/verzinkt	
										9-966140-1 F		966140-1 F			2	7	TAB (25.4mm)	CuSn4	TINNED/verzinkt	
										9-966140-2 F		966140-2 F			5	1	21 POS. HOUSING	PA66-GF13	NATURAL/natur	
18	5	33.5	25	40	37.5	33.5	31.5			9-966140-3 F		966140-3 F		18.3g	4	7	TAB (43.4mm)	CuSn4	TINNED/verzinkt	
										9-966140-4 F		966140-4 F			3	7	TAB (34.4mm)	CuSn4	TINNED/verzinkt	
										9-966140-5 F		966140-5 F			2	7	TAB (25.4mm)	CuSn4	TINNED/verzinkt	
15	4	28.5	20	35	32.5	28.5	26.5			9-966140-6 F		966140-6 F		16.0g	1	1	21 POS. HOUSING	PA66-GF13	BLACK/schwarz	
										9-966140-7 F		966140-7 F			4	6	TAB (43.4mm)	CuSn4	TINNED/verzinkt	
										9-966140-8 F		966140-8 F			3	6	TAB (34.4mm)	CuSn4	TINNED/verzinkt	
12	3	23.5	15	30	27.5	23.5	21.5		B (GROOVES) Nuten A-C A (GROOVES B-C) (Nuten B-C)		9-966140-9 F		966140-9 F		13.6g	2	6	TAB (25.4mm)	CuSn4	TINNED/verzinkt
											9-966140-10 F		966140-10 F			1	1	18 POS. HOUSING	PA66-GF13	BLACK/schwarz
										9-966140-11 F		966140-11 F		4		5	TAB (43.4mm)	CuSn4	TINNED/verzinkt	
										9-966140-12 F		966140-12 F		3		5	TAB (34.4mm)	CuSn4	TINNED/verzinkt	
9	2	18.5	10	25	22.5	18.5	16.5			9-966140-13 F		966140-13 F		11.2g	2	5	TAB (25.4mm)	CuSn4	TINNED/verzinkt	
										9-966140-14 F		966140-14 F			1	1	15 POS. HOUSING	PA66-GF13	BLACK/schwarz	
										9-966140-15 F		966140-15 F			4	4	TAB (43.4mm)	CuSn4	TINNED/verzinkt	
6	1	13.5	5	20	17.5	13.5	11.5			9-966140-16 F		966140-16 F		8.9g	3	4	TAB (34.4mm)	CuSn4	TINNED/verzinkt	
										9-966140-17 F		966140-17 F			2	3	TAB (34.4mm)	CuSn4	TINNED/verzinkt	
										9-966140-18 F		966140-18 F			3	3	TAB (25.4mm)	CuSn4	TINNED/verzinkt	
										9-966140-19 F		966140-19 F			1	1	9 POS. HOUSING	PA66-GF13	BLACK/schwarz	
POSITIONS Polzahl	n	a±0.2	b	c	d _{-0.2}	e _{-0.25}	f	B (GROOVES) Nuten A-C A (GROOVES B-C) (Nuten B-C)			9-966140-20 F		966140-20 F		6.6g	4	2	TAB (43.4mm)	CuSn4	TINNED/verzinkt
										9-966140-21 F		966140-21 F		3		2	TAB (34.4mm)	CuSn4	TINNED/verzinkt	
										9-966140-22 F		966140-22 F		2		2	TAB (25.4mm)	CuSn4	TINNED/verzinkt	
										9-966140-23 F		966140-23 F		1		1	6 POS. HOUSING	PA66-GF13	BLACK/schwarz	
POSITIONS Polzahl	n	a±0.2	b	c	d _{-0.2}	e _{-0.25}	f		CODING Kodierung	CAVITY NUMBERING Kammerbezeichnung	ORDER NO. REV. Bestell-Nr.	ORDER NO. REV. Bestell-Nr.	WEIGHT Gewicht	POS.	QTY Stueck	DESCRIPTION Benennung Einzelteil	MATERIAL Werkstoff	SURFACE/Oberflaeche		
																		COLOUR/ Farbe		