

LMK00725EVM User's Guide

User's Guide



Literature Number: SNOU126
September 2013

1	Introduction	4
2	Features	4
3	Setup	4
	3.1 Input/ Output Connector Description	4
4	Operation	5
5	PCB Layout	7
6	Schematic	11
7	Bill of Materials	12

List of Figures

1	LMK00725 Input Structure and Default Input Termination	5
2	Top Layer	7
3	Inner Layer 2 (Ground Plane, Inverted)	8
4	Inner Layer 3 (Supply Plane, Inverted)	9
5	Bottom Layer	10
6	LMK00725EVM Schematic	11

List of Tables

1	Device and Package Configurations	4
2	LMK00725EVM Bill of Materials	12

LMK00725EVM User's Guide

1 Introduction

The LMK00725 is a low skew, high performance clock fanout buffer, which distributes up to five 3.3 V LVPECL outputs. The clocks are derived from one of two selectable inputs, which can accept differential or single-ended input signals.

This evaluation module (EVM) is designed to demonstrate the functionality and electrical performance of the LMK00725 device. For optimum performance, the board is equipped with 50-ohm SMA connectors and 50-ohm controlled impedance traces.

Table 1. Device and Package Configurations

DESIGNATOR	IC	PACKAGE
U1	LMK00725	PW-20 (TSSOP 20 pin)

2 Features

- Easy to use evaluation board to fan-out up to five LVPECL clocks with low phase noise/jitter
- Accepts differential or single-ended/LVCMOS input clock
- Device control pins configurable through jumpers
- Board power at 3.3-V for VCC

3 Setup

This section describes the jumpers and connectors on the EVM as well and how to properly connect, set up and use the LMK00725EVM.

With this EVM, one could distribute one of two input clocks to up to 5 LVPECL outputs. Therefore, a minimum of one clock source is needed and appropriate test equipment to observe or measure the outputs.

3.1 Input/ Output Connector Description

Connectors:

- **CLK0** and **nCLK0** SMA connectors are used to interface an external AC-coupled clock input to the first of the two differential input pairs (CLK0, nCLK0) of the device.
- **CLK1** and **nCLK1** SMA connectors are used to interface an external AC-coupled clock input to the second of the two differential input pairs (CLK1, nCLK1) of the device..
- **Q1**, **nQ1** and **Q3**, **nQ3** SMA connectors are used to distribute two of the five differential clock outputs. The other three differential clock outputs are not connected to the traces, so their SMA connectors are not populated by default.
- **PWR** is a 3-pin header used to 3.3-V supply power to the board/device. VCC and GND pins are labeled on the top side of the board. The center pin is not connected (N/C).

Jumpers:

- **CLK-SEL** selects between one of two inputs.
 - 0 (position 1-2) = Select CLK0, nCLK0 inputs
 - 1 (position 2-3) = Select CLK1, nCLK1 inputs
- **CLK-EN** selects between U1 clock enabled or disabled modes.
 - 0 (position 1-2) = Clock Disabled
 - 1 (position 2-3) = Clock Enabled (normal operation)

4 Operation

Power:

Before, applying any clock inputs, supply the board with 3.3 V and ground at VCC and GND pins of the PWR header. Make sure the supply current being drawn is less than 115 mA.

Inputs:

Figure 1 shows the LMK00725 input structure. The internal 51 k Ω pull-up and pull-down resistors work with the external 50 Ω termination resistors, which bias the device inputs to mid-rail. Therefore, AC-coupled clock sources from 0.15Vpp to 1.3Vpp (50 Ω terminated) can be tied to either of the two differential clock inputs. With the default input termination shown in Figure 1, the input SMAs expect a 100 Ω differential clock source. Note that with the default input configuration, the differential input has only very small offset voltage (~3.2 mV) so that when the selected clock inputs are left open/floating, the outputs could have the tendency to chatter.

With DC-coupled clock sources, use a “DC-block” at the input SMAs to ensure DUT input voltage range compliance. Alternatively, adjust the clock source DC bias (if available) to make sure the LMK00725 input voltage range is not violated.




Figure 1. LMK00725 Input Structure and Default Input Termination

The clock inputs can accommodate a differential input or single-ended input signal with the proper external input termination using the various component options on the board. Refer to the datasheet for input interface application circuits.


To achieve the best possible additive jitter and noise floor performance, it is recommended to drive the CLK/nCLK pair using an input signal with fast slew rate of 3 V/ns (differential) or higher. Driving the input with a lower slew rate can degrade the additive jitter and noise floor performance. For this reason, a differential input signal (e.g. LVPECL), is recommended because it typically provides higher slew rate and common-mode noise rejection compared to a single-ended input (LVCMOS/LVTTL or sine-wave, for example).

Outputs:

By default, two of the five LVPECL output pairs are connected to the traces and SMA connectors via series 0- Ω resistors. The remaining three LVPECL pairs are not connected to the traces (0- Ω resistors not installed) and thus do not have SMA connectors installed. The routed outputs have 180- Ω bias resistors to ground and are AC-coupled to the SMA connectors to allow direct connections to RF instruments via SMA cables for test and evaluation. The AC-coupled outputs should be terminated with single-ended 50 Ω or 100 Ω differential loads.


To minimize reflections and signal integrity issues, it is recommended to terminate any driven output trace with a 50- Ω SMA load termination, or otherwise disconnect any unused output from the trace by removing the 0- Ω series resistor (R30 to R39).

5 PCB Layout




ALL ARTWORK VIEWED FROM TOP SIDE	BOARD #: SU600949	REV: A	SUN REV: Not In VersionControl
LAYER NAME = Top Layer			
PLOT NAME = Top Layer	GENERATED : 8/29/2013 12:19:38 PM	TEXAS INSTRUMENTS	

Figure 2. Top Layer




ALL ARTWORK VIEWED FROM TOP SIDE	BOARD #: SU600949	REV: A	SUN REV: Not In VersionControl
LAYER NAME = GNDPL2	Pink Outline		
PLOT NAME = Layer 2	GENERATED : 8/29/2013 12:19:39 PM	TEXAS INSTRUMENTS	

Figure 3. Inner Layer 2 (Ground Plane, Inverted)



ALL ARTWORK VIEWED FROM TOP SIDE	BOARD #: SU600949	REV: A	SUN REV: Not In VersionControl
LAYER NAME = VccBL3 d Outline			
PLOT NAME = Layer 3	GENERATED : 8/29/2013 12:19:40 PM	TEXAS INSTRUMENTS	


Figure 4. Inner Layer 3 (Supply Plane, Inverted)



ALL ARTWORK VIEWED FROM TOP SIDE	BOARD #: SU600949	REV: A	SUN REV: Not In VersionControl
LAYER NAME = Bottom Layer			
PLOT NAME = Bottom Layer	GENERATED : 8/29/2013 12:19:40 PM	TEXAS INSTRUMENTS	

Figure 5. Bottom Layer

6 Schematic



Revision History	
Revision	Notes

Figure 6. LMK00725EVM Schematic

7 Bill of Materials

Table 2. LMK00725EVM Bill of Materials

Designator	Qty	Value	Description	Pkg Ref	Part Number	Manufacturer
!PCB	1		Printed Circuit Board		SV600949	Any
C1	1	10uF	CAP, CERM, 10uF, 10V, +/-10%, X5R, 0805	0805	C0805C106K8PACTU	Kemet
C2, C6, C8, C14, C16, C18, C21, C22, C30, C31, C33, C36	12	0.1uF	CAP, CERM, 0.1uF, 16V, +/-5%, X7R, 0603	0603	0603YC104JAT2A	AVX
C11, C13, C29	3	0.1uF	CAP, CERM, 0.1uF, 10V, +/-10%, X5R, 0402	0402	C1005X5R1A104K	TDK
C12	1	1uF	CAP, CERM, 1uF, 10V, +/-10%, X5R, 0603	0603	C1608X5R1A105K	TDK
CLKEN, CLKSEL, PWR	3	1x3	Header, TH, 100mil, 1x3, Gold plated, 230 mil above insulator	PBC03SAAN	PBC03SAAN	Sullins Connector Solutions
CLK0, CLK1, nCLK0, nCLK1, nQ1, nQ3, Q1, Q3	8	50 Ohm	Connector, SMT, End launch SMA 50 ohm	SMA	142-0701-806	Emerson Network Power
CLKEN_2-3, CLKSEL_1-2	2	1x2	Shunt, 100mil, Gold plated, Black	Shunt	969102-0000-DA	3M
FID1, FID2, FID3	3		Fiducial mark. There is nothing to buy or mount.	Fiducial	N/A	N/A
GND1, GND2	2	Black	Test Point, TH, Compact, Black	Keystone 5006	5006	Keystone
H1, H2, H3, H4	4		Machine Screw, Round, #4-40 x 1/4, Nylon, Philips panhead	Screw	NYPMS4400025PH	B&F Fastener Supply
H5, H6, H7, H8	4		Standoff, Hex, 0.5"L #4-40 Nylon	Standoff	1902C	Keystone
LBL1	1		Thermal Transfer Printable Labels, 0.650" W x 0.200" H - 10,000 per roll	PCB Label 0.650"H x 0.200"W	THT-14-423-10	Brady
R2, R7, R12, R17, R32, R33, R36, R37	8	0	RES, 0 ohm, 5%, 0.1W, 0603	0603	CRCW06030000Z0EA	Vishay-Dale
R4, R6, R15, R16	4	49.9	RES, 49.9 ohm, 1%, 0.1W, 0603	0603	CRCW060349R9FKEA	Vishay-Dale
R9, R11	2	1.0k	RES, 1.0k ohm, 5%, 0.1W, 0603	0603	CRCW06031K00JNEA	Vishay-Dale
R40, R41, R42, R43, R44, R45, R46, R47, R48, R49	10	180	RES, 180 ohm, 1%, 0.1W, 0603	0603	RC0603FR-07180RL	Yageo America
U1	1		Low Skew, 1-to-5, Differential-to-3.3V LVPECL Fanout Buffer, PW0020A	PW0020A	LMK00725PW	Texas Instruments
C7, C17, C23, C32	0	0.1uF	CAP, CERM, 0.1uF, 16V, +/-5%, X7R, 0603	0603	0603YC104JAT2A	AVX
nQ0, nQ2, nQ4, Q0, Q2, Q4	0	50 Ohm	Connector, SMT, End launch SMA 50 ohm	SMA	142-0701-806	Emerson Network Power

Table 2. LMK00725EVM Bill of Materials (continued)

Designator	Qty	Value	Description	Pkg Ref	Part Number	Manufacturer
R3, R8, R13, R18	0	100	RES, 100 ohm, 1%, 0.1W, 0603	0603	CRCW0603100RFKEA	Vishay-Dale
R30, R31, R34, R35, R38, R39	0	0	RES, 0 ohm, 5%, 0.1W, 0603	0603	CRCW06030000Z0EA	Vishay-Dale

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

Products

Audio	www.ti.com/audio
Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DLP® Products	www.dlp.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
OMAP Applications Processors	www.ti.com/omap
Wireless Connectivity	www.ti.com/wirelessconnectivity

Applications

Automotive and Transportation	www.ti.com/automotive
Communications and Telecom	www.ti.com/communications
Computers and Peripherals	www.ti.com/computers
Consumer Electronics	www.ti.com/consumer-apps
Energy and Lighting	www.ti.com/energy
Industrial	www.ti.com/industrial
Medical	www.ti.com/medical
Security	www.ti.com/security
Space, Avionics and Defense	www.ti.com/space-avionics-defense
Video and Imaging	www.ti.com/video

TI E2E Community

e2e.ti.com