



## Wiha Insulated Nut Drivers



**322 Nut Driver, With Wiha-SoftFinish® Handle Insulation**  
According to ASTM F-1505-01, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E, up to 1000 Volt. Individually Tested. Blade CVM steel, hardened. Insulation molded directly onto blade. Deep drawn 1" socket. Wiha-SoftFinish® handle, multi-component.

| Item No. | mm   | mm  | mm  | Inch | lbs. | pkg. |
|----------|------|-----|-----|------|------|------|
| 322 06   | 4.0  | 125 | 236 | 9.3  | .15  | 10   |
| 322 09   | 5.0  | 125 | 236 | 9.3  | .16  | 10   |
| 322 12   | 5.5  | 125 | 236 | 9.3  | .16  | 10   |
| 322 15   | 6.0  | 125 | 236 | 9.3  | .16  | 10   |
| 322 18   | 7.0  | 125 | 243 | 9.6  | .25  | 10   |
| 322 21   | 8.0  | 125 | 243 | 9.6  | .25  | 10   |
| 322 24   | 9.0  | 125 | 243 | 9.6  | .25  | 10   |
| 322 27   | 10.0 | 125 | 243 | 9.6  | .27  | 10   |
| 322 30   | 11.0 | 125 | 243 | 9.6  | .37  | 10   |
| 322 33   | 12.0 | 125 | 243 | 9.6  | .38  | 10   |
| 322 36   | 13.0 | 125 | 243 | 9.6  | .39  | 10   |



**322 Nut Driver, With Wiha-SoftFinish® Handle. Inch sizes.**

| Item No. | Inch  | Inch | mm  | Inch | lbs. | pkg. |
|----------|-------|------|-----|------|------|------|
| 322 55   | 5/32  | 5.0  | 236 | 9.3  | .15  | 10   |
| 322 58   | 3/16  | 5.0  | 236 | 9.3  | .15  | 10   |
| 322 61   | 7/32  | 5.0  | 236 | 9.3  | .16  | 10   |
| 322 64   | 1/4   | 5.0  | 243 | 9.5  | .24  | 10   |
| 322 67   | 5/16  | 5.0  | 243 | 9.5  | .25  | 10   |
| 322 68   | 11/32 | 5.0  | 242 | 9.5  | .26  | 10   |
| 322 70   | 3/8   | 5.0  | 243 | 9.5  | .26  | 10   |
| 322 73   | 7/16  | 5.0  | 243 | 9.5  | .36  | 10   |
| 322 76   | 1/2   | 5.0  | 243 | 9.5  | .39  | 10   |
| 322 78   | 9/16  | 5.0  | 243 | 9.5  | .39  | 10   |
| 322 80   | 5/8   | 5.0  | 243 | 9.5  | .41  | 10   |

| Item No. | Inch   | Inch  | Inch | Inch   | lbs.     |
|----------|--------|-------|------|--------|----------|
| 322 96   | 322 55 | 5/32  | 5.0  | 322 70 | 3/8 5.0  |
|          | 322 58 | 3/16  | 5.0  | 322 73 | 7/16 5.0 |
|          | 322 61 | 7/32  | 5.0  | 322 76 | 1/2 5.0  |
|          | 322 64 | 1/4   | 5.0  | 322 78 | 9/16 5.0 |
|          | 322 67 | 5/16  | 5.0  | 322 80 | 5/8 5.0  |
|          | 322 68 | 11/32 | 5.0  |        |          |

1000Volt SHOP

### Warning!

Insulated tools are not intended for use on live or energized circuits. Always disconnect and de-energize all equipment & circuits. **NEVER!** work on live or energized circuits or equipment.

### Use & Care Guide For Insulated Tools:

Store tools to minimize risk of damage to insulation  
Inspect insulation prior to each use of any insulated tool  
If you doubt the integrity of the insulation destroy the tool or have it retested  
Use insulated tools where the ambient temperature is between -20 to +70° C  
Have a qualified safety technician inspect and re-certify tools annually for safe use



| Item No. | mm     | mm  | mm  | mm     | lbs.     |
|----------|--------|-----|-----|--------|----------|
| 322 91   | 322 15 | 6.0 | 125 | 322 24 | 9.0 125  |
|          | 322 18 | 7.0 | 125 | 322 27 | 10.0 125 |
|          | 322 21 | 8.0 | 125 |        |          |



| Item No. | mm     | mm  | mm  | mm     | lbs.     |
|----------|--------|-----|-----|--------|----------|
| 322 93   | 322 09 | 5.0 | 125 | 322 21 | 8.0 125  |
|          | 322 12 | 5.5 | 125 | 322 27 | 10.0 125 |
|          | 322 15 | 6.0 | 125 | 322 36 | 13.0 125 |
|          | 322 18 | 7.0 | 125 |        |          |



| Item No. | Inch   | Inch | Inch | Inch   | lbs.    |
|----------|--------|------|------|--------|---------|
| 322 92   | 322 61 | 7/32 | 5.0  | 322 70 | 3/8 5.0 |
|          | 322 64 | 1/4  | 5.0  | 322 76 | 1/2 5.0 |
|          | 322 67 | 5/16 | 5.0  |        |         |



| Item No. | Inch   | Inch | Inch | Inch   | lbs.     |
|----------|--------|------|------|--------|----------|
| 322 94   | 322 58 | 3/16 | 5.0  | 322 70 | 3/8 5.0  |
|          | 322 61 | 7/32 | 5.0  | 322 73 | 7/16 5.0 |
|          | 322 64 | 1/4  | 5.0  | 322 76 | 1/2 5.0  |
|          | 322 67 | 5/16 | 5.0  |        |          |